		SATCO 'I NUVO'
Project Name		
Location	Prepared By	
SSACO LICE WILLIAMOUS		
CATCO	0726	
SATCO S 14T8/LED/48-840/DR GL/		

Notes

rw1 09-09-2025 21:52

General	<u></u>
Status	Discontinued
Substitute	S49936R1
Watts	14W
Incandescent Equivalent	100W
Fluorescent Equivalent	25W-32W
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	1800L
Beam Spread	230
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	May not be compatible with all rapid start, dimmable, and emergency ballasts; Ballast required; Approved for enclosed fixtures whe used only on low or normal ballast factor systems
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	48
MOD	1
Lens Finish	Gloss White
Lens Finish	Gloss Write
Additional Information	
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years
Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
None Compliant	
FCC Compliant	Yes
FCC Compliant SDS Sheet	Yes LED_Lamp