SATCO' NUVO

Project Name

Prepared By



SATCO S9737 14T8/LED/48-850/DR GLASS

Notes

General	
Status	Discontinued
Substitute	S49937R1
Watts	14W
Incandescent Equivalent	100W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1800L
Beam Spread	230
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Pallacting Poquiroments	May not be compatible with all rapid start, dimmable, and emergency ballasts; Ballast
Ballasting Requirements	required; Approved for enclosed fixtures when used only on low or normal ballast factor systems
Operating Temperature	used only on low or normal ballast factor
	used only on low or normal ballast factor systems
Operating Temperature	used only on low or normal ballast factor systems
Operating Temperature Physical	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F)
Operating Temperature Physical MOL	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48
Operating Temperature Physical MOL MOD Lens Finish	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1
Operating Temperature Physical MOL MOD Lens Finish Additional Information	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White
Operating Temperature Physical MOL MOD Lens Finish	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures.
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years cULus Damp
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status RoHS Compliant	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	used only on low or normal ballast factor systems -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale