

Project Name

Location

Prepared By



SATCO S9749

9T8/LED/24-850/DR GLASS

Notes

(revised) 07-09-2023 000-19-02

General

Status	Discontinued
Substitute	S49949
Watts	9W
Incandescent Equivalent	75W
Fluorescent Equivalent	17W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Gloss White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1150L
Beam Spread	230
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	May not be compatible with all rapid start, dimmable, and emergency ballasts.; Ballast required; Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	24
MOD	1
Lens Finish	Gloss White

Additional Information

Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp