SATCO' NUVO

Project Name

Prepared By



SATCO S9751 40W/LED/HID/MB/5000K/100-277V

Notes

General	
Status	Discontinued
Substitute	S39751
Watts	40W
Incandescent Equivalent	300W
Fluorescent Equivalent	65W
	175W
HID Equivalent	120V-277V
Volts	
Shape	Corncob Maguel Extended
Base	Mogul Extended
ANSI Base	EX39
	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	5200L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 8.27 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Working Voltage	AC 90-305V
Operating Frequency	50-60Hz
Power Factor	>.9
Operating Position	Universal
Operating Tereserature	200 (45) (
Operating Temperature	-20C (-4F) to +65C (+149F)
Physical	-20C (-4F) to +65C (+149F)
	-20C (-4F) to +65C (+149F) 7.88
Physical	
Physical MOL	7.88
Physical MOL MOD	7.88 3.5
Physical MOL MOD Lens Finish Housing Color	7.88 3.5 Clear
Physical MOL MOD Lens Finish Housing Color Additional Information	7.88 3.5 Clear White
Physical MOL MOD Lens Finish Housing Color	7.88 3.5 Clear
Physical MOL MOD Lens Finish Housing Color Additional Information	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.;
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in.
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale
Physical MOL MOD Lens Finish Housing Color Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status RoHS Compliant	7.88 3.5 Clear White Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 8.88 inches 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale

Copyright 2023 Satco Products, Inc. All Rights Reserved

