SATCO NUVO

Project Name

Location

Prepared By



Notes

ww] 01-15-2024 02:40:1

Hawaii Status

Nevada Status

Vermont Status

RoHS Compliant

FCC Compliant

Washington Status

General	
Status	Active
Watts	10W
Incandescent Equivalent	90W
HID Equivalent	30W
Volts	12V-24V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1200L
Beam Spread	330
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 8.50 in. Width: 6 in. Depth: 6 in.
Electrical	
Working Voltage	12V-24V DC Only
	12V-24V DC Only 50Hz
Working Voltage	
Working Voltage Operating Frequency	50Hz
Working Voltage Operating Frequency Operating Position	50Hz Universal
Working Voltage Operating Frequency Operating Position Operating Temperature	50Hz Universal
Working Voltage Operating Frequency Operating Position Operating Temperature Physical	50Hz Universal -25C (-13F) to +45C (+113F)
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL	50Hz Universal -25C (-13F) to +45C (+113F) 5.81
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance	Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64 5 Year Limited - Hi-Pro
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64 5 Year Limited - Hi-Pro
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50Hz Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64 5 Year Limited - Hi-Pro Not Applicable Damp
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star	Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64 5 Year Limited - Hi-Pro Not Applicable Damp No
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64 5 Year Limited - Hi-Pro Not Applicable Damp No No
Working Voltage Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	Universal Universal -25C (-13F) to +45C (+113F) 5.81 2.44 Clear White/Grey Yes IP64 5 Year Limited - Hi-Pro Not Applicable Damp No No No No

Lawful for sale

Lawful for sale

Lawful for sale

Lawful for sale

Yes

Yes

SDS Sheet LED_Lamp	

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



