## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S9799**

60W/LED/HID/MB/2700K/100-277V

Notes

www] 01-15-2024 02:40:1

CA T20 / T24 Rationale

California Status

| General   |   |
|---|---|
| Status  | Discontinued  |
| Substitute  | S39799  |
| Watts   | 60W   |
| Incandescent Equivalent   | 500W  |
| Fluorescent Equivalent  | 85W   |
| HID Equivalent  | 250W  |
| Volts   | 100V-277V   |
| Shape   | Corncob   |
| Base  | Mogul Extended  |
| ANSI Base   | EX39  |
| Finish  | Clear   |
| CCT (Kelvin)  | 2700K   |
| Temperature   | Warm White  |
| CRI   | 83  |
| Lumens  | 7320L   |
| Beam Spread   | 360   |
| Dimmable  | Non-Dimmable  |
| Hours Rated   | 50000   |
| Lamp Type   | Corncob   |
| Technology  | LED   |
| Min Compartment Size  | Length: 8.27 in. Width: 9.25 in.<br>Depth: 9.25 in.   |
| Ballasting Requirements   | Ballast Bypass  |
| Electrical  |   |
|   |   |
| Working Voltage   | AC 90-305V  |
| Working Voltage Operating Frequency   | AC 90-305V<br>50-60Hz   |
|   |   |
| Operating Frequency   | 50-60Hz   |
| Operating Frequency Power Factor  | 50-60Hz<br>0.9  |
| Operating Frequency Power Factor Operating Position   | 50-60Hz<br>0.9<br>Universal   |
| Operating Frequency Power Factor Operating Position Operating Temperature   | 50-60Hz<br>0.9<br>Universal   |
| Operating Frequency Power Factor Operating Position Operating Temperature Physical  | 50-60Hz<br>0.9<br>Universal<br>-20C (-4F) to +65C (+149F)   |
| Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL  | 50-60Hz 0.9 Universal -20C (-4F) to +65C (+149F)  8.56  |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD   | 50-60Hz 0.9 Universal -20C (-4F) to +65C (+149F)  8.56 3.81   |
| Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color  | 50-60Hz 0.9 Universal -20C (-4F) to +65C (+149F)  8.56 3.81 Clear   |
| Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish  | 50-60Hz 0.9 Universal -20C (-4F) to +65C (+149F)  8.56 3.81 Clear White  Width 360 deg 3.8 in.; Width 270   |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information  Additional Info  | 50-60Hz 0.9 Universal -20C (-4F) to +65C (+149F)  8.56 3.81 Clear White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Additional Info   | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information  Additional Info  | 50-60Hz 0.9 Universal -20C (-4F) to +65C (+149F)  8.56 3.81 Clear White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating   | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  IP65  Arms fully open diameter is 10.88   |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Installation Notes  Warranty  | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  IP65  Arms fully open diameter is 10.88 inches  |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information  Additional Info Rated For Enclosed Fixture IP Rating Installation Notes  Warranty  Compliance                                | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  IP65  Arms fully open diameter is 10.88 inches  5 Year Limited - Hi-Pro               |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Installation Notes  Warranty  Compliance  Safety Listing              | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  IP65  Arms fully open diameter is 10.88 inches  5 Year Limited - Hi-Pro               |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information  Additional Info Rated For Enclosed Fixture IP Rating Installation Notes  Warranty  Compliance Safety Listing Location Rating | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  IP65  Arms fully open diameter is 10.88 inches  5 Year Limited - Hi-Pro  cUllus  Damp |
| Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Installation Notes  Warranty  Compliance  Safety Listing              | 50-60Hz  0.9  Universal -20C (-4F) to +65C (+149F)  8.56  3.81  Clear  White  Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in.  Yes  IP65  Arms fully open diameter is 10.88 inches  5 Year Limited - Hi-Pro               |

Exempt - Base Not Regulated

Lawful for sale in California

| Title 20 / 24 Status | Lawful for sale |
|----------------------|-----------------|
| Colorado Status      | Lawful for sale |
| Hawaii Status        | Lawful for sale |
| Nevada Status        | Lawful for sale |
| Washington Status    | Lawful for sale |
| Vermont Status       | Lawful for sale |
| RoHS Compliant       | Yes             |
| FCC Compliant        | Yes             |
| SDS Sheet            | LED_Lamp        |

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



