

Project Name

Location Prepared By



Notes

9WPLH/LED/835/DR/2P

SATCO S9855

w] 08-26-2025 22:

Status	Active
Watts	9W
Fluorescent Equivalent	26W
Volts	Ballast Dependent
Ballast Type	Туре А
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	850L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Horizontal
Technology	LED
Electrical	
Ballasting Requirements	Ballast required
Operating Frequency	60Hz

Electrical	
Ballasting Requirements	Ballast required
Operating Frequency	60Hz
Power Factor	0.83
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	6.63
MOD	1.09
Housing Color	White
Weight (lb.)	0.18

Additional Information	
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp