SATCO NUVO

Project Name

ocation Prepared By



Notes

w1 07-02-2025 00:52:2

General	
Status	Discontinued
Substitute	S21300
Watts	3.5W
Incandescent Equivalent	40W
Volts	120V
Shape	CA11
Base	Candelabra
ANSI Base	E12
Finish	Frost
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	350L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	60Hz
Operating Prequency Operating Position	60Hz Universal
Operating Frequency Operating Position Operating Temperature	60Hz Universal -20C (-4F) to +45C (+113F)
Operating Position Operating Temperature	Universal
Operating Position Operating Temperature Physical	Universal -20C (-4F) to +45C (+113F)
Operating Position Operating Temperature Physical MOL	Universal -20C (-4F) to +45C (+113F) 5
Operating Position Operating Temperature Physical MOL MOD	Universal -20C (-4F) to +45C (+113F) 5 1.38
Operating Position Operating Temperature Physical MOL	Universal -20C (-4F) to +45C (+113F) 5
Operating Position Operating Temperature Physical MOL MOD	Universal -20C (-4F) to +45C (+113F) 5 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	Universal -20C (-4F) to +45C (+113F) 5 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29618
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29618 Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29618 Lawful for sale Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29618 Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status Vermont Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29618 Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status Washington Status	Universal -20C (-4F) to +45C (+113F) 5 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29618 Lawful for sale

LED_Lamp

SDS Sheet