SATCO NUVO

Project Name

Location Prepared By



Notes

www] 05-15-2024 04:42:5

General	
Status	Discontinued
Substitute	S39902
Watts	9W
Incandescent Equivalent	75W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Туре А
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	82
Lumens	1150L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant
	Startand Rapid Start ballasts with no rewiring required
Operating Frequency	•
Operating Frequency Power Factor	no rewiring required
	no rewiring required 50/60Hz
Power Factor	no rewiring required 50/60Hz 0.9
Power Factor Operating Temperature	no rewiring required 50/60Hz 0.9
Power Factor Operating Temperature Physical	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1
Power Factor Operating Temperature Physical MOL MOD Lens Finish	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus -
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified Damp
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified Damp No
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified Damp No No
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified Damp No No Exempt - Base Not Regulated
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified Damp No No Exempt - Base Not Regulated Lawful for sale in California
Power Factor Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status	no rewiring required 50/60Hz 0.9 -20C (-4F) to +45C (+113F) 24 1 Frost White 0.24 Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs cULus - Classified; cULus - Certified Damp No No Exempt - Base Not Regulated Lawful for sale Lawful for sale

Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



