

Project Name

Location

Prepared By



SATCO S9910

25T5/LED/46-840/DR

Notes

(www) 09-09-2023 21:03:49

General

Status	Discontinued
Substitute	S29910
Watts	25W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	3500L
Beam Spread	185
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	48
MOD	0.63
Lens Finish	Gloss White

Additional Information

Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus - Classified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp