

Project Name

ocation Prepared By



Notes

w] 08-18-2025 00:09:

Status	Discontinued	
Substitute	S29919	
Watts	43W	
Incandescent Equivalent	125W	
Fluorescent Equivalent	54W/59W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	Т8	
Base	Single Pin	
ANSI Base	Fa8	
Nominal Length	96	
Finish	Gloss White	
CCT (Kelvin)	5000K	
Temperature	Natural Light	
CRI	80+	
Lumens	5500L	
Beam Spread	210	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	96
MOD	1
Lens Finish	Gloss White
Weight (lb.)	0.91

Shatter-Proof Type	Yes
Silatter-Proof Type	162
Installation Notes	Not for use in vapor tight fixtures
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp