

Notes

SATCO S9933

15T8U6/LED/22.5-850/BP

w] 10-27-2025 05:20

General	
Status	Discontinued
Substitute	S18413
Watts	15W
Incandescent Equivalent	100W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.5
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1800L
Beam Spread	220
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	U-Bend
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	22.5

Physical	
MOL	22.5
MOD	1
Leg Spacing	6
Lens Finish	Frost

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp