

Project Name

Prepared By



Notes

Obsolete
S49934R1
11.5W
60W
25W-32W
Ballast Dependent
Туре А
Т8
Medium Bi Pin
G13
48
Gloss White
3000K
Warm White
80+
1700L
220
Non-Dimmable
50000
Linear
LED
May not be compatible with all rapid start
ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Startand Rapid Start ballasts with no rewiring
Startand Rapid Start ballasts with no rewiring required
Startand Rapid Start ballasts with no rewiring required 0.95
Startand Rapid Start ballasts with no rewiring required 0.95
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F)
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures.
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures.
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years cULus Damp No
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years CULus Damp No Lawful for sale in California Lawful for sale
Startand Rapid Start ballasts with no rewiring required 0.95 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. 5-Years cULus Damp No Lawful for sale in California Lawful for sale Lawful for sale

ilistaliation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years
Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp