

Project Name

Location

Prepared By



**Notes**

[www] 03-31-2023 09:32:29

General	
Status	Discontinued
Substitute	S49936R1
Watts	11.5W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	1800L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	May not be compatible with all rapid start, dimmable, and emergency ballasts.; Ballast required; Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.96
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	48
MOD	1
Lens Finish	Gloss White

Additional Information	
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - T8 LED Bulbs

Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp