

Notes

Status	Active	
Watts	23W	
Fluorescent Equivalent	40W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T5	
Base	2G11	
ANSI Base	2G11	
Finish	Frost	
CCT (Kelvin)	3500K	
Temperature	Neutral White	
CRI	80+	
Lumens	2800L	
Beam Spread	270	
Hours Rated	50000	
Product Category	PL	
Operating Position	Universal	
Technology	LED	

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	

·, s.ca.	
MOL	22.5
MOD	0.63
Housing Color	White
Weight (lb.)	0.38

Additional Information	
Additional Info	CCT Selectable Option: S18423
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	Yes
DLC ID	P007T912
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp