

Project Name

Location

Prepared By



**Notes**

[www] 05-15-2024 04:42:59

**General**

Status	Active
Substitute	S18423
Watts	23W
Fluorescent Equivalent	40W
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	2G11
ANSI Base	2G11
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	82
Lumens	2800L
Beam Spread	270
Hours Rated	50000
Product Category	PL
Operating Position	Universal
Technology	LED

**Electrical**

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

**Physical**

MOL	22.5
MOD	0.63
Housing Color	White

**Additional Information**

Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

**Compliance**

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PL2ISZU5GTZN
NSF Approved	Yes
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale

RoHS Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.  
All Rights Reserved

For More Information Visit:  
<https://www.satco.com/>

