

Project Name

Location

Prepared By



SATCO S9952

15PLL/LED/835/BP

Notes

(revised) 07-09-2023 000-19-02

General

Status	Active
Watts	15W
Fluorescent Equivalent	36W
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	2G11
ANSI Base	2G11
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1900L
Beam Spread	270
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20% (+/-5%)
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	16.5
MOD	0.68
Housing Color	White
Weight (lb.)	0.31

Additional Information

Additional Info	CCT Selectable Option: S18422
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp