SATCO NUVO

Project Name

ocation Prepared By



Notes

rw1 07-07-2025 00:12:3

General	
Status	Discontinued
Substitute	S21318
Watts	5.5W
Incandescent Equivalent	60W
Volts	120V
Shape	CA11
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	500L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz 0.9
Power Factor	0.9
Power Factor Operating Position Operating Temperature	0.9 Universal
Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F) 4.31
Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years cULus Damp
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S21284
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S21284 Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S21284 Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S21284 Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status Vermont Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S21284 Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.31 1.38 0.05 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S21284 Lawful for sale Lawful for sale Lawful for sale



Yes

LED_Lamp

FCC Compliant

SDS Sheet