

Project Name

Prepared By



Notes

General	
Status	Discontinued
Substitute	S49977R1
Watts	15W
Incandescent Equivalent	100W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens Roam Enroad	2200L 220
Beam Spread Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
	LLD
Electrical	
Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Power Factor	0.97
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	48
MOD	1
Lens Finish	Gloss White
Additional Information	
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years
Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes

