

Project Name

Location

Prepared By



## SATCO S9489

36W/LED/HID/AMBER/100-277V E26

### Notes

(www) 18-27-2023 05:20:50

### General

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| Status                  | Active                                           |
| Substitute              | S13138                                           |
| Watts                   | 36W                                              |
| Incandescent Equivalent | 200W                                             |
| Fluorescent Equivalent  | 55W                                              |
| HID Equivalent          | 150W                                             |
| Volts                   | 120V-277V                                        |
| Shape                   | Corn cob                                         |
| Base                    | Medium                                           |
| ANSI Base               | E26                                              |
| Finish                  | Clear                                            |
| CCT (Kelvin)            | 1461K                                            |
| Lumens                  | 4140L                                            |
| Beam Spread             | 300                                              |
| Dimmable                | Non-Dimmable                                     |
| Hours Rated             | 50000                                            |
| Product Category        | Corn cob                                         |
| Technology              | LED                                              |
| Min Compartment Size    | Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in. |
| Ballasting Requirements | Ballast Bypass- Direct wire only 100V-277V       |

### Electrical

|                       |                            |
|-----------------------|----------------------------|
| Working Voltage       | AC 90-305V                 |
| Operating Frequency   | 50-60Hz                    |
| Power Factor          | >0.9                       |
| Operating Position    | Universal                  |
| Operating Temperature | -20C (-4F) to +65C (+149F) |

### Physical

|               |            |
|---------------|------------|
| MOL           | 9.25       |
| MOD           | 3.69       |
| Lens Finish   | Clear      |
| Housing Color | White/Grey |

### Additional Information

|                            |                                      |
|----------------------------|--------------------------------------|
| Additional Info            | Amber color - 585nm                  |
| Rated For Enclosed Fixture | Yes                                  |
| IP Rating                  | IP65                                 |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Warranty                   | 5-Years                              |

### Compliance

|                      |                                   |
|----------------------|-----------------------------------|
| Safety Listing       | cULus - Certified; cULus - Listed |
| Location Rating      | Damp                              |
| DLC Approved         | No                                |
| California Status    | Lawful for sale in California     |
| Title 20 / 24 Status | Lawful for sale                   |
| Colorado Status      | Lawful for sale                   |
| Hawaii Status        | Lawful for sale                   |
| Nevada Status        | Lawful for sale                   |
| Vermont Status       | Lawful for sale                   |
| Washington Status    | Lawful for sale                   |
| RoHS Compliant       | Yes                               |
| FCC Compliant        | Yes                               |
| SDS Sheet            | LED_Lamp                          |